

a world of energy

INDUSTRIAL SE ESSENTIALS

RESIDENTIAL & 餐 COMMERCIAL 第

HE NOVICE













AVAILABLE IN BRANCH OI ONLINE AT REXEL.CO.UK



INDUSTRIAL ESSENTIALS, BUT NOT JUST FOR INDUSTRY!



At Rexel, understanding our customers needs is at the heart of everything we do. We recognise that each customer has their own specific needs relevant to the sector. Whether you're a contractor, installer, or end user, we are here to collaborate with you every step of the way, understanding your needs, and offering personalised support, innovative products, and expert guidance to help you thrive in the ever-changing, demanding markets of today.

ESSENTIALS ESSENTIALS





Our new extensive range of control gear has been designed to address those challenging breakdown situations, tailored specifically for contractors and installers in both commercial and residential sectors, not just our industrial specialist customers.

Whether its power outages or equipment failures, our control gear empowers professionals to:

- Manage emergency situations swiftly and effectively
- Restore power quickly in commercial offices and minimising disruptions to business operations
- · Ensure safety and security for residential buildings
- Keep essential systems running smoothly in retail spaces
- Safeguard power supplies to healthcare facilities that rely on an uninterrupted power supply, safeguarding patients care and comfort
- Support education institutions by minimising downtime in classrooms and facilities to uphold the continuity of learning and operations

ALL THE RIGHT PRODUCTS AND ADVICE YOU NEED, WHEN YOU NEED IT



Rexel, as your partner of choice, will be right by your side when you are facing such challenges, providing expert support, and unrivalled stock availability. The range is stocked in over 200 Rexel branches, and if you need an unusual or discontinued part, we have the specialist teams to source quickly for you. Visit Rexel today for peace of mind, knowing that we have the products and solutions to be your trusted partner. Explore our range today and elevate your capability to respond to any challenge with confidence.

STEEL ENCLOSED CONTACTORS Newlect

- Manufactured in accordance with EN60947-4-1
- IP55 steel enclosure
- Standard coil voltage: 230V 50/60Hz
- · Auxiliary contacts can be fitted
- · Colour RAL7035 light grey
- Knockouts top and bottom
- All units are suitable for two wire control i.e. time switch, thermostat, sensor or other remote controls
- · Supplied complete with neutral terminals



Order No.	Model No.	AC1 Heating & General Load	Fluorescent Mercury	Halogen	LED	No. of Poles	Dimensions HxWxD
STEEL ENCLOSED CONTACTORS							
1051042857	NLCONM25/4	25A	16A	13A	25A	4 + N	184 x 184 x 149mm
1051042858	NLCONM45/4	40A	27A	22A	40A	4 + N	184 x 184 x 149mm
1051042859	NLCONM63/3N	60A	40A	32A	60A	3 + N	305 x 285 x 159mm

DIRECT ON LINE, REVERSING & STAR DELTA STARTERS

- Manufactured in accordance with EN60947-4-1
- IP55 steel enclosure
- Colour RAL7035 light grey
- Surface mounting
- Standard coil voltages: 230V or 400V 50/60Hz
- \bullet Built in start/stop and reset push button
- Hand reset thermal overloads
- · Overload to be ordered separately
- · Stainless steel pozidrive fixing screws for lid
- Knockouts top and bottom
- Internal components DIN rail mounted

Newlec⁻



NLSTM27C

Order No.	Model No.	Max Rating	Control Voltage	Dimensions H x W x D	Type
DIRECT ON LIN	E & REVERSING STA	RTERS			
1051042849	NLSTM27C	7.5kW	230V	174 x 104 x 134mm	Direct on Line
1051042850	NLSTM47C	7.5kW	400V	174 x 104 x 134mm	Direct on Line
1051042856	NLRVM45C	5.5kW	400V	184 x 184 x 149mm	Reversing
1051042851	NLSTM25CSW	5.5kW	230V	184 x 184 x 149mm	DOL With Isolator
1051042852	NLSTM45CSW	5.5kW	400V	184 x 184 x 149mm	DOL With Isolator
1051042854	NLSDM415C	15kW	400V	184 x 284 x 149mm	Star Delta































3 POLE CONTACTORS

Newlec⁻

- Manufactured in accordance with EN60947-4-1
- DIN rail mount
- · Contactors include built in N/O auxiliary
- · Auxiliaries 10A thermal current rated 660V AC max
- Simple and robust construction
- · High mechanical & electrical life
- · Full range of add on accessories







NLC32230

Order No.	Model No.	Amp Rating @ 400V AC1	Amp Rating @ 400V AC3	Voltage	Frame Size			
3 POLE CONTACTORS								
2501174483	NLC9024	25	9	24VAC	1			
2501174484	NLC12024	25	12	24VAC	1			
2501174485	NLC18024	25	18	24VAC	1			
2501174486	NLC32024	40	32	24VAC	2			
1051042867	NLC9230	25	9	230VAC	1			
1051042868	NLC12230	25	12	230VAC	1			
1051042869	NLC18230	25	18	230VAC	1			
1051042870	NLC32230	40	32	230VAC	2			
1051042871	NLC9400	25	9	400VAC	1			
1051042874	NLC32400	40	32	400VAC	2			

AUXILIARIES FOR CONTACTORS

Newlec⁻



NLCAUX11



NLCAUX11S



NLCAUX22

OVERLOADS

Newlec.

- Manufactured in accordance with EN60947-4-1
- UL approved
- · Manual overload reset
- Class 10 tripping curve (up to 60°C)
- Integrated auxiliary contacts (1 N/O and 1 N/C)
- Type 2 compatible with contactor



NLOLC5

			0 1 11		Amp	Range	To Fit
Order No.	Model No.	Description	Order No.	Model No.	From	To	Frame Size
AUXILIARIES	FOR CONTAC	CTORS	OVERLOADS				
1051042875	NI CAUXII	Auxiliary Contact Top Mount	1051042839	NLOLC1	1A	1.6A	1 & 2
10510428/5 NLCAUXII	NECAOXII	1NO + 1NC	1051042840	NLOLC2	1.6A	2.5A	1 & 2
1051042876	NLCAUX22	Auxiliary Contact Top Mount	1051042841	NLOLC3	2.5A	4.0A	1 & 2
		2NO + 2NC	1051042842	NLOLC4	4.0A	6.0A	1 & 2
1051042877	NLCAUX11S	Auxiliary Contact Side Mount 1NO +1NC	1051042843	NLOLC5	5.5A	8.0A	1 & 2
	INO TINE	1051042844	NLOLC6	7.0A	10A	1 & 2	
			1051042845	NLOLC7	10A	13A	1 & 2
			1051042846	NLOLC8	13A	18A	1 & 2
			1051042847	NLOLC9	18A	25A	1 & 2
			1051042848	NLOLC10	23A	32A	2

PUSH BUTTON STATIONS

Newlec⁻

- Manufactured in accordance with EN60947-5-1, EN60947-5-5 where applicable
- IP65 rated (when correctly installed)
- M20/PG16 gland entries
- 22mm push button range made for tough environments
- · Insulated self extinguishing ABS plastic housing
- · Common auxiliaries throughout push button range
- · Space for an additional contact block on each actuator
- Light grey lid / dark grey base (yellow lid for Estop)
- · Stainless steel captive screws
- · Supplied with 1 contact per actuator



NLESTOP37ENC



NLESTOP60ENC



NLESTOPPALM

Order No.	Model No.	Description	Contact Included
PUSH BUTTO	N STATIONS		
1051042861	NLESTOP37ENC	Emergency Stop Twist Release 37mm	1 x NC
1051042862	NLESTOP60ENC	Emergency Stop Twist Release 60mm	1 x NC
1051042863	NLESTOPKRENC	Emergency Stop Key Release 37mm	1 x NC
1051042864	NL2POSKSENC	2 Position Key Switch	1 x NO
1051042866	NLSSENC	Start/Stop	1 x NO/1 x NC
1051042865	NLSENC	Start	1 x NO

PUSH BUTTON STATION ENCLOSURES

Newlec⁻

- IP65 rated (when correct pushbutton device installed
- · Insulated self extinguishing ABS plastic housing



Order No.	Model No.	Description
PUSH BUTTON	STATION ENCL	OSURES
1051042878	NLPBENC1	Pushbutton Enclosure 22mm 1 Way Grey IP65
1051042879	NLPBENC2	Pushbutton Enclosure 22mm 2 Way Grey IP65



































ACTUATORS 22MM

Newlec.

- Manufactured in accordance with EN60947-5-1, EN60947-5-5 where applicable
- IP65 rated (when correctly installed)
- Modular design for total flexibility
- Compatible with enclosed push button stations
- Operating temperature -25 to +70°C
- · Screw fit contacts
- Contact blocks rating 250V/5A (ordered separately)
- Up to 4 contact blocks can be fitted

Newlec⁻

- 50.000 hours service life
- Manufactured in accordance with EN60947-5-1

PILOT LIGHTS 22MM - LED

- IP65 rated (when correctly installed)
- 230VAC & 24VAC/DC rated LED
- · Other voltages available to order
- Operating temperature -25 to +70°C















NLCPBESTOP

NLCPBG

Order No.	Model No.	Description
ACTUATORS	22MM	
1051042885	NLCPBESTOP	Emergency Stop Twist Release 37mm
2501174494	NLCPBESTOPKR	Emergency Stop Key Release 37mm
1051042887	NLCPBG	Green Push Button
1051042888	NLCPBR	Red Push Button, Raised
1051042886	NLCPBB	Black Push Button
2501174495	NLCPBKS2	2 Position Stay Put Key Switch Actuator 22mm
1051042890	NLCPBKS	3 Position Stay Put Key Switch Actuator 22mm
2501174496	NLCPBSS2	2 Position Stay Put Selector Switch Actuator 22mm
1051042889	NLCPBSS	3 Position Stay Put Selector Switch Actuator 22mm

Oraer No.	Model No.	Colour
PILOT LIGHTS	22MM - LED - 24	VAC/DC
2501174490	NLCINDG24	Green
2501174491	NLCINDR24	Red
2501174487	NLCINDA24	Amber
2501174488	NLCINDB24	Blue
2501174489	NLCINDC24	Clear
PILOT LIGHTS	22MM - LED - 23	OVAC
1051042880	NLCINDG	Green
1051042881	NLCINDR	Red
1051042882	NLCINDA	Amber
1051042883	NLCINDB	Blue
1051042884	NLCINDC	Clear

CONTACT BLOCKS

Newlec⁻

• Fits all Newlec pushbuttons and pushbutton stations

Order No.	Model No.	Description
CONTACT BL	OCKS	
1051042891	NLPBAUXNC	Push Button Contact 1NC
1051042892	NLPBAUXNO	Push Button Contact 1NO



MULTI FUNCTION TIMER



- Manufactured to EN 61812-1, EN 61010-1
- · CE & UL approved
- Multi voltage 12 to 240VAC/DC
- 8 Amp switching capability
- · Single pole change over contact
- 7 selectable functions
- Time range 0.1 seconds to 100 hours
- · DIN rail mounted
- 17.5mm width



Order No.	Model No.	Description
MULTI FUNCT	ION TIMER	
1052080258	H3D-M	Multi Function Timer

PLUG IN RELAYS - BASES



- Manufactured to IEC 61810-1
- UL approved
- · Surface or DIN rail mount
- · Supplied with marking tab



Order No.	Model No.	No. of Pins	Relay
PLUG IN RELA	YS - BASES		
2500811598	10FF-2Z-C3	8	NLCR2
1052080256	10FF-3Z-C3	11	NLCR3
2500811594	18FF-4Z-C7	14	NLCR4

INDUSTRIAL PLUG IN RELAYS



- Manufactured to IEC 61810-1
- UL approved
- · Industry standard octal plug in relays
- Built in lockable test button, flag indicator and LED
- 10 Amp switching capability (4 pole switching 5 Amp)
- High electrical endurance (100,000 operations)
- · AgSn02 (Cadmium-free) contacts
- · Other voltages available to order



R2-24VDC



Z4-24VAC

					24-24 VAC
Order No.	Model No.	No. of Pins	No. of Poles	Contact Rating	Voltage
INDUSTRIAL P	LUG IN RELAYS				
2501599116	R2-12VDC	8	2	10A	12V DC
2501599127	R2-24VDC	8	2	10A	24V DC
2501599129	R2-24VAC	8	2	10A	24V AC
2501599130	R2-110VAC	8	2	10A	110V AC
2501599131	R2-240VAC	8	2	10A	230V AC
2501599134	R3-24VDC	11	3	10A	24V DC
2501599133	R3-24VAC	11	3	10A	24V AC
2501599135	R3-110VAC	11	3	10A	110V AC
2501599117	R3-240VAC	11	3	10A	230V AC
2501510243	Z4-24VDC	14	4	5A	24V DC
2501510241	Z4-24VAC	14	4	5A	24V AC
2501510239	Z4-110VAC	14	4	5A	110V AC
2501510242	Z4-240VAC	14	4	5A	230V AC









































Newlec⁻

- ATEX approved
- · Wemid insulating material
- · UL 94 VO flammability rating

TERMINAL PACKS -

35MM TOP HAT RAIL

- Uniform accessories for 2.5mm and 4mm
- · Vibration resistant connection
- · Patented clamping yoke system



NLTERM2.5/35 NLTERMPK2.5/35





NLTERM4.0/35

NLTERMEARTH4/35

Order No.	Model No.	Conductor Size	Terminals	Earth Terminals	End Stop	End Plate
TERMINAL P	ACKS - 35MM TOP HAT RA	AIL				
1050151150	NLTERM2.5/35	2.5mm ²	10	-	2	1
1050151151	NLTERM4.0/35	4mm²	10	-	2	1
1050150467	NLTERMPK2.5/35	2.5mm ²	8	2	2	1
1050150469	NLTERMEARTH4/35	4mm²	-	10	-	-
1030130403	NETERIIEAR III4/33	4111111		10		

TERMINAL RAIL

Manufactured and approved to DIN 46277-3/EN 50022



Order No.	Model No.	Profile	Length (M)	Slotted
TERMINAL RAI	L			
1000009370	NLRAIL35	В	0.5	-
1050152844	NLRAIL35S	В	2	Yes
1050152846	NLRAIL3515S	С	2	Yes
1050152847	NLRAILASB	NA	Rail Suppo	rt Bracket

Newlec.



CABLE MARKER KITS

- · Self extinguishing PVC
- Temperature range -45°C to +70°C
- · Chemical resistant
- Mixed Marker Kit NLCM1KIT Contains 200 of each colour coded markers: 0-9 (Coloured), L, N, R, S, T, +, -, Earth (White) and 1 applicator
- Black and White Marker Kit NLCM2KIT Contains 200 of each black & white markers: A-Z, O-9, +, -, Earth, Full Stop, Blank, L1, L2, L3 and 1 applicator
- Black and Yellow Marker Kit K Type NLCM3KIT Contains 100 of each black & yellow markers: A-Z, 0-9, +, -, /, Earth. Also contains 200 x 12 digit carrier strips and 100 x 7 digit carrier strips
- · Marker replenishment packs available

Order No.	Model No.	Description
CABLE MARKE	R KITS	
1052073578	NLCM1KIT	Mixed Marker 0.75 - 6.0mm
1052073582	NLCM2KIT	B/W Marker 0.75 - 6.0mm
1052073615	NLCM3KIT	Black & Yellow Marker K Type





























Newlec⁻

- Compliance with IEC 670
- Ideal for heavy duty applications in difficult working and climatic conditions
- IK9 impact resistance
- Operating temperature: -15°C to +60°C
- Integral mounting grids and integral sealing gasket
- RAL 7035 grey
- Back mounting plate also available



				_
Order No.	Model No.	External Dimensions H x W x D	Hinged Lid	Mounting Plate~(not included)
STANDARD I	P65			
1050151831	NLPE10A	100 x 100 x 60mm	-	-
1050151832	NLPE20A	120 x 80 x 60mm	-	-
1050151833	NLPE30A	150 x 100 x 60mm	-	-
1050151834	NLPE40A	190 x 140 x 70mm	-	1050151839/NLPEBP40
1050151835	NLPE50A	240 x 190 x 90mm	-	1050151840/NLPEBP50
1050151837	NLPE70A	300 x 220 x 120mm	Yes	1050151842/NLPEBP70
1050151838	NLPE80A	380 x 300 x 120mm	Yes	1050151843/NLPEBP80
HIGH LID IP5	5			
1051056588	NLPE15HL	110 x 110 x 112mm	-	1051056594/NLPEBP15
1051056589	NLPE30HL	150 x 110 x 150mm	-	1051056595/NLPEBP30
1051056590	NLPE35HL	150 x 150 x 150mm	-	1051056596/NLPEBP35
1050151836	NLPE60HL	220 x 150 x 150mm	-	1050151841/NLPEBP60
CLEAR LID IP	55			
1051056591	NLPE40CL	190 x 140 x 70mm	-	1050151839/NLPEBP40
1051056592	NLPE50CL	240 x 190 x 90mm	-	1050151840/NLPEBP50
1051056593	NLPE70CL	300 x 220 x 150mm	-	1050151842/NLPEBP70

GRP WALL MOUNT ENCLOSURES

Newlec⁻

- Ingress protection IP66
- Enclosures include back plate
- Colour RAL7035



Order No.	Model No.	Dimensions HxWxD
GRP ENCLOSU	RES	
2501375469	NLGRP352515AX	350x250x150mm
2501375470	NLGRP403020AX	400x300x200mm
2501375471	NLGRP404020AX	400x400x200mm
2501375472	NLGRP604020AX	600x400x200mm
2501375473	NLGRP606020AX	600x600x200mm
2501375474	NLGRP806030AX	800x600x300mm





POWER SUPPLIES

SCL

- Manufactured to EN 55022 class B and EN6100-3-2.3
- UL Approved
- DIN Rail mount
- Input Voltage range 85-264VAC
- Output voltage 24VDC
- · Power on LED

Order No.	Model No.	Description
POWER SUPP	PLIES	
2501163528	NDR-60-24	2.5A 60W 24VDC
2501163538	NDR-120-24	5A 120W 24VDC
2501163539	NDR-240-24	10A 240W 24VDC



Newlec - CLIMATE CONTROL

Newlec-









NLMELOCKHAX

NLMELOCKAX

Order No.	Model No.	Description	Order No.	Model No.	Description
ENCLOSURE -	CLIMATE CONT	ROL	ENCLOSURE -	ACCESSORIES	
2500907737	NLENCH20W	Heater 18-20W	2501375476	NLGRPMBRKTAX	Wall Brackets for GRP
2500907738	NLENCH50W	Heater 49-50W	2501575470	NEOKI FIBRATIAN	Enclosure (PK4)
2500907739	NLENCTHERM	Thermostat +5 to +60 Degrees C	2501192385	NLMEMBRKTAX	Wall Mount Bracket for Steel Enclosures (PK 4)
2500907774	NLFAN20M	Fan 230VAC 20/25 m³/H at 50/60 Hz	2501375477	NLGRPLOCKHAX	Handle for GRP Enclosures to be used with NLMELOCKAX
2500907732	NLFILTER20	Outlet Filter for NLFAN2OM			
2500907733	NLFAN55M	FAN 230VAC 55/66 m³/H AT 50/60 Hz	2501306531	NLMELOCKHAX	Handle for Steel Enclosures to be used with NLMELOCKAX
2500907734	NLFILTER55	Outlet Filter for FAN55M			Key Lock for Enclosures
2500907735	NLFAN105M	Fan 230VAC 105/120 m³/H at 50/60 Hz	2501192384	NLMELOCKAX	Requires Handle NLLOCKHAX
2500907736	NI FILTER105	Outlet Filter for NI FAN105M			

STEEL WALL MOUNT ENCLOSURES STEEL TERMINAL BOXES

Newlec⁻

- Ingress protection IP66
- All round foamed-in PU door seal
- Colour RAL 7035
- · Gland plate on base
- · Includes zinc plated mounting plate



Order No.	Model No.	Dimensions HxWxD
STEEL ENCLO	SURES	
2501192376	NLME303021AX	300x300x210mm
2501192378	NLME383821AX	380x380x210mm
2501192377	NLME403021AX	400x300x210mm
2501192379	NLME504021AX	500x400x210mm
2501192380	NLME505021AX	500x500x210mm
2501192381	NLME603821AX	600x380x210mm
2501192382	NLME606025AX	600x600x250mm

Newlec.

- · Protection category IP66
- · Steel sheet enclosure
- · All round foamed-in PU cover seal
- Colour RAL7035






NLMEB202012KX

NLMTB151580KX

Order No.	Model No.	Dimensions HxWxD
STEEL TERMI	NAL BOXES - HINGE	LID - BACKPLATE INCLUDED
2501197270	NLMEB151580KX	150x150x80mm
2501197271	NLMEB202012KX	200x200x120mm
2501197272	NLMEB302012KX	300x200x120mm
2501197273	NLMEB303012KX	300x300x120mm
2501197274	NLMEB403012KX	400x300x120mm
2501192375	NLMEB302015KX	300x200x155mm
STEEL TERMI	NAL BOXES - SCREW	/ LID - NO BACKPLATE
2501197275	NLMTB151580KX	150x150x80mm
2501197275	NLMTB151580KX	150x150x80mm
2501197275 2501197277	NLMTB151580KX NLMTB151512KX	150x150x80mm 150x150x120mm
2501197275 2501197277 2501197279	NLMTB151580KX NLMTB151512KX NLMTB153012KX	150x150x80mm 150x150x120mm 150x300x120mm
2501197275 2501197277 2501197279 2501197276	NLMTB151580KX NLMTB151512KX NLMTB153012KX NLMTB202080KX	150x150x80mm 150x150x120mm 150x300x120mm 200x200x80mm



Our terms and conditions of sale apply to the sale of goods to the exclusion of all other terms. A copy of our terms is available at www.rexel.co.uk. The information in this document is for general information purposes only. Rexel UK Limited assumes no responsibility in so far as the law permits for errors or omissions in the contents of this document. No reliance shall be placed on the contents by readers.

300x400x120mm

2501197282 NLMTB304012KX

All information correct at time of going to print. E. & O.E. Unless indicated otherwise, all equipment featured in this catalogue is produced by third party manufacturers.































Fabrication

A flexible, bespoke nationwide service to suit your specific requirements, from basic cutting to large scale complex solutions



The benefits of working with our team:

- Bespoke design
- Time and cost-saving
- High quality products through leading manufacturers
- Competitive rates
- Reduce your H&S risks
- · Increase your flexibility
- Over 30 years of industry expertise and experience
- Nationwide delivery

Services we offer:

Distribution Unit

Board Assemblies

Customisation: Pre-wired & pre-mounted

- Trapezes. H Frames
- Length Cutting: Rod, Basket, Tray
 - Luminaires
- Floor Boxes
- · Solar switchgear housing
- EV charging cabinets
- Enclosure modifications
- Control units

Cable Harnessing

Making life easier on site

